

Container Cafe - Technical Specifications and Price List

Canonical URL: <https://www.samanportable.com/product/container-cafe>

Six approved sizes and prices

SIZE	AREA (SQ FT)	COVERS	RATE EX-GST	EX-GST	INCL. 18% GST
10x10x8.5 ft	100	8 diners	INR 2,035/sq ft	INR 2,03,500	INR 2,40,130
20x8x8.5 ft	160	13 diners	INR 2,035/sq ft	INR 3,25,600	INR 3,84,208
20x10x8.5 ft	200	17 diners	INR 1,850/sq ft	INR 3,70,000	INR 4,36,600
20x12x8.5 ft	240	20 diners	INR 1,776/sq ft	INR 4,26,240	INR 5,02,963
30x10x8.5 ft	300	25 diners	INR 1,776/sq ft	INR 5,32,800	INR 6,28,704
40x10x8.5 ft	400	33 diners	INR 1,739/sq ft	INR 6,95,600	INR 8,20,808

Base specification price - customisations quoted separately. Ex-factory, ex-GST.

Steel Structure

COMPONENT	DETAIL
Bottom frame	125x75x4 mm or 150x75x5 mm MS C-channel
Bottom stiffeners	100x50x3–4 mm channels with counter and equipment reinforcement
Floor frame	80x40x3 mm or 100x50x3 mm primary floor supports
Top frame	80x40x3 mm MS top perimeter
Roof stiffeners	60x40x2.5 mm roof members with exhaust and signage supports
Corner posts / walls	60x60x3 mm posts with façade and counter framing
Lifting / handling	Designed MS lifting hooks or lugs matched to the completed unit weight; handle only by the approved lifting and support-point drawing.
Welding & fabrication	Welded MS fabrication with cleaned joints, safe edges, dimensional inspection and coating touch-up before panel closure and dispatch.

Walls, Roof, Floor & Insulation

COMPONENT	DETAIL
Exterior walls	1.2–1.6 mm corrugated MS structural sheet with decorative over-cladding
Roof	1.4–1.6 mm corrugated MS sheet
Interior walls	8–10 mm fibre-cement board, HPL or stainless-steel lining in food-service zones
Ceiling	Washable fibre-cement, ACP, PVC or metal-liner ceiling
Floor base	18–24 mm cement fibre board with waterproof treatment
Floor finish	Anti-skid tile, 3–4 mm PU/epoxy or 2.5 mm safety vinyl
Wall insulation	50–75 mm mineral wool
Roof insulation	75–100 mm mineral wool
Decorative / external finish	4 mm ACP, 6–8 mm HPL, WPC or wooden-finish metal over-cladding above the mandatory corrugated MS structural shell.
Fasteners & sealing	Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it.

Doors, Windows, Electrical & Services

COMPONENT	DETAIL
Main door / service door	Staff/customer door plus lockable service counter or shutter.
Windows / service opening	Large aluminium service glazing with lockable counter opening.
Grills / mosquito mesh	Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it.
Electrical wiring	Concealed PVC-insulated copper wiring, typically 1.5 sq.mm lighting, 2.5 sq.mm sockets and 4 sq.mm higher-load or AC circuits, subject to the final load schedule.
Electrical protection	Distribution board with MCB/RCCB protection, earthing and segregation of lighting, socket, wet-area and AC circuits according to the approved electrical drawing.

COMPONENT	DETAIL
Electrical fittings	LED lighting, signage supply, multiple 6A/16A appliance sockets, dedicated equipment circuits and DB/MCB protection.
Ventilation / AC	Exhaust-hood/duct provision, fresh-air opening and optional AC for the customer zone.
Plumbing / sanitary	Sink/handwash, CPVC water supply, UPVC waste and equipment connection points according to layout.
Layout / configuration	Front service counter with separate staff preparation and storage zones.
Painting / coating	One red-oxide primer coat followed by two compatible anti-rust enamel coats on prepared MS surfaces; project exposure may require an upgraded coating system.
Quality checks	Pre-dispatch checks cover dimensions, member and sheet identification, welds, coating, roof drainage, weather sealing, doors, windows, electrical continuity and functional operation.
Warranty	5-year structural warranty and 1-year finishing warranty as standard; finishing warranty extendable to 2 years on request, confirmed at quotation. Relocation damage, misuse, site services and unapproved alterations remain outside the agreed scope unless stated otherwise.

Warranty and contacts

Warranty: 5-year structural warranty and 1-year finishing warranty as standard; finishing warranty extendable to 2 years on request, confirmed at quotation. Relocation damage, misuse, site services and unapproved alterations remain outside the agreed scope unless stated otherwise.

South: +91 88616 22859 | sales@samanportable.com

North: +91 87960 39938 | ncr@samanportable.com

Generated: 08 August 2026