

Container Restaurant - Technical Specifications and Price List

Canonical URL: <https://www.samanportable.com/product/container-cafe/container-restaurant>

Six approved sizes and prices

SIZE	AREA (SQ FT)	COVERS	RATE EX-GST	EX-GST	INCL. 18% GST
10x10x8.5 ft	100	8 diners	INR 2,200/sq ft	INR 2,20,000	INR 2,59,600
20x8x8.5 ft	160	13 diners	INR 2,200/sq ft	INR 3,52,000	INR 4,15,360
20x10x8.5 ft	200	17 diners	INR 2,000/sq ft	INR 4,00,000	INR 4,72,000
40x8x8.5 ft	320	27 diners	INR 1,880/sq ft	INR 6,01,600	INR 7,09,888
40x10x8.5 ft	400	33 diners	INR 1,880/sq ft	INR 7,52,000	INR 8,87,360
40x12x8.5 ft	480	40 diners	INR 1,840/sq ft	INR 8,83,200	INR 10,42,176

Base specification price - customisations quoted separately. Ex-factory, ex-GST.

Steel Structure

COMPONENT	DETAIL
Bottom frame	150x75x5 mm MS C-channel or engineered built-up base
Bottom stiffeners	100x50x4 mm channels with local cooking-equipment and counter supports
Floor frame	100x50x3 mm primary and 80x40x3 mm secondary floor members
Top frame	80x40x3 mm MS top perimeter
Roof stiffeners	60x40x3 mm roof members with hood, duct and signage reinforcement
Corner posts / walls	60x60x3 mm posts with wide service-opening reinforcement
Lifting / handling	Designed MS lifting hooks or lugs matched to the completed unit weight; handle only by the approved lifting and support-point drawing.
Welding & fabrication	Welded MS fabrication with cleaned joints, safe edges, dimensional inspection and coating touch-up before panel closure and dispatch.

Walls, Roof, Floor & Insulation

COMPONENT	DETAIL
Exterior walls	1.6 mm corrugated MS structural sheet with ACP/HPL/WPC/wood-finish over-cladding
Roof	1.6 mm corrugated MS sheet
Interior walls	10–12 mm fibre-cement board with stainless-steel kitchen-zone lining
Ceiling	8–10 mm fibre-cement or 0.50 mm washable metal-liner ceiling
Floor base	24 mm cement board with waterproofing
Floor finish	Anti-skid tile, 3–4 mm PU flooring or heavy safety vinyl
Wall insulation	75 mm mineral wool
Roof insulation	100 mm mineral wool
Decorative / external finish	4 mm FR-grade ACP/HPL façade, service canopy, signage frame and stainless-steel kitchen-zone lining.
Fasteners & sealing	Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it.

Doors, Windows, Electrical & Services

COMPONENT	DETAIL
Main door / service door	Staff/customer door plus lockable service counter or shutter.
Windows / service opening	Large aluminium service glazing with lockable counter opening.
Grills / mosquito mesh	Security grill, insect mesh, guard, louver or protection selected only where the approved use and opening schedule requires it.
Electrical wiring	Concealed PVC-insulated copper wiring, typically 1.5 sq.mm lighting, 2.5 sq.mm sockets and 4 sq.mm higher-load or AC circuits, subject to the final load schedule.

COMPONENT	DETAIL
Electrical protection	Distribution board with MCB/RCCB protection, earthing and segregation of lighting, socket, wet-area and AC circuits according to the approved electrical drawing.
Electrical fittings	LED lighting, signage supply, multiple 6A/16A appliance sockets, dedicated equipment circuits and DB/MCB protection.
Ventilation / AC	Exhaust-hood/duct provision, fresh-air opening and optional AC for the customer zone.
Plumbing / sanitary	Sink/handwash, CPVC water supply, UPVC waste and equipment connection points according to layout.
Layout / configuration	Front service counter with separate staff preparation and storage zones.
Painting / coating	One red-oxide primer coat followed by two compatible anti-rust enamel coats on prepared MS surfaces; project exposure may require an upgraded coating system.
Quality checks	Pre-dispatch checks cover dimensions, member and sheet identification, welds, coating, roof drainage, weather sealing, doors, windows, electrical continuity and functional operation.
Warranty	5-year structural warranty and 1-year finishing warranty as standard; finishing warranty extendable to 2 years on request, confirmed at quotation. Relocation damage, misuse, site services and unapproved alterations remain outside the agreed scope unless stated otherwise.

Warranty and contacts

Warranty: 5-year structural warranty and 1-year finishing warranty as standard; finishing warranty extendable to 2 years on request, confirmed at quotation. Relocation damage, misuse, site services and unapproved alterations remain outside the agreed scope unless stated otherwise.

South: +91 88616 22859 | sales@samanportable.com

North: +91 87960 39938 | ncr@samanportable.com

Generated: 08 August 2026